

# Information on discontinued models

Information on discontinued models is provided below.  
For further information on standard specifications,  
please refer to the catalog before use.

## Information on discontinued models

Discontinued model	Nominal size	Date of sale discontinuation	Date of discontinuation of parts supply	Recommended alternative model
<b>&lt;High Performance Butterfly Valve&gt;</b>				
<b>336Y</b>	350~600mm	2000.05.01	2005.04.30	<b>302A</b>
<b>331Y</b>	80~300mm	2000.05.01	2005.04.30	<b>304A</b>
<b>&lt;Chemically Resistant Butterfly Valves&gt;</b>				
<b>841T</b>	250*300mm	2012.10.31	2017.10.31	<b>846T</b>
<b>842T</b>	250*300mm	2004.05.01	2009.04.30	<b>847T</b>
<b>841T</b>	50~200mm	2001.06.01	2006.05.31	<b>50mm:847T 65~200mm:846T</b>
<b>842T</b>	50~200mm	1999.12.01	2004.11.30	<b>847T</b>
<b>&lt;Rubber Seated Valves&gt;</b>				
<b>773Z</b>	40~300mm	2014.04.01	2019.03.31	<b>700Z</b>
<b>731X • 732X</b>	350~600mm	2013.09.03	—	<b>731P • 732P</b> Model names integrated, but no change in product specification
<b>SF490A</b> Dacrotized Disc (700G*705G*704G)	65mm	2008.11	2009.10	<b>SCS14</b> (Ribbed) valve disc
<b>702Z</b>	40~300mm	2004.05.01	2009.04.30	<b>773Z</b>
<b>700S</b>	50~600mm (550mm available)	2004.05.01	2009.04.30	<b>700G 705G</b>
<b>732X</b>	50~300mm	2000.10.01	2005.09.30	<b>731P*732P</b>
<b>731X</b>	50~300mm	1999.01.05	2003.12.31	<b>731P*732P</b>
<b>641B</b>	50~200mm	1999.06.01	2004.05.31	—
<b>720F</b>	50~800mm	1999.06.01	2004.06.01	<b>50~100mm:704G 125~800mm:722F</b>
<b>731X</b>	350~400mm	1999.01.05	2003.12.31	<b>732X</b>
<b>700E</b>	50~600mm	1998.04.01	2003.03.31	<b>700G*700S</b> (550mm only)
<b>&lt;Check Valves&gt;</b>				
<b>904C</b>		2010.07.31	2010.07.31	<b>908H</b>
Discontinued model		Date of sale discontinuation	Date of discontinuation of parts supply	Recommended alternative model
<b>&lt;Motorized Actuator&gt;</b>				
<b>PMK080SRM</b>		2009.06.30	2010.06.30	<b>PMK-100CR</b>
<b>SRE</b>		2005.12.31	2010.12.30	<b>SRJ</b>
<b>PMK030SRM</b>		2003.07.31	2006.07.31	<b>PMK-030CR</b>
<b>MICOM ELMY</b>		1997.03.01	2002.02.28	<b>New MICOM ELMY</b>
<b>&lt;Pneumatic Actuator&gt;</b>				
<b>T-matic</b>		2006.10.31	2011.10.30	<b>T-DYNAMO</b>
<b>Z cylinder</b>		2000.07.01	2005.06.30	<b>T-DYNAMO</b>
<b>&lt;Manual Actuator&gt;</b>				
<b>1G lever</b>		2004.06.01	2009.05.31	<b>1T lever</b>
<b>2M gear</b>		2000.09.01	2000.09.01	<b>2U gear</b>
<b>1M lever</b>		1997.10.01	2002.09.30	<b>1T lever</b>

# Our Coating Standard

Standard Specifications
Approvals
Handling Precautions

We provide a coating (surface treatment) that meets the general environment standard in the following table. For use in areas susceptible to damage by salt, such as places close to the sea, please ask for the special coating shown in the following table.

## Coating Selection Table (A) by Valve Installation Environment

Valve : 700G, 700GB Bore 300mm or less  
846T, 847T Bore 250mm  
Actuator : 1T, 2U

Item	Specification	General environment	Special specification	
		Indoor/outdoor specification	Salt damage resistant specification	Heavy salt damage resistant specification
Usage environment		General indoors/outdoors	Outdoors at distance of least 300 m but no more than 1 km from the shore	Outdoors in coastal regions within 300m from the shore
Applied material		※1 JIS type 2 scraping	Same as on the left	※2 JIS type 1 scraping
Applied coating	Undercoat	Polyester epoxy powder coating	Same as on the left	Zinc rich primer
	Overcoat			Epoxy resin coating
				Polyurethane resin coating

## Coating Selection Table (B) by Valve Installation Environment

Valve : 700S, 7004G (FCD body), 705G, 731P, 732P Bore 300mm or less  
846T, 847T Bore 200mm  
508V Bore 350mm or less  
Actuator : TGA • TG-S cylinder 6Z diaphragm

Item	Specification	General environment	Special specification	
		Indoor/outdoor specification	Salt damage resistant specification	Heavy salt damage resistant specification
Usage environment		General indoors/outdoors	Outdoors at distance of least 300 m but no more than 1 km from the shore	Outdoors in coastal regions within 300m from the shore
Surface preparation		※1 JIS type 2 scraping	Same as on the left	※2 JIS type 1 scraping
Applied coating	Undercoat	Epoxy resin coating (solvent)	Epoxy resin coating (solvent)	Zinc rich primer
	Overcoat		Polyurethane resin coating	Epoxy resin coating
				Polyurethane resin coating

● For use in a severe installation environment such as around a cooling tower, overcoat (epoxy) is recommended.

※1: Equivalent to ISO St3  
※2: Equivalent to ISO St2.5